

# MATERIAL SAFETY DATA SHEET

MSDS 0121

## Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	C-Flux	HMIS CODES	Health 2
		Flammability	1
		Reactivity	0
PRODUCT CODES	74025, 74026	PPI	B
CHEMICAL FAMILY:	Organic/Inorganic		
USE	Soldering Flux		
MANUFACTURER'S NAME	The RectorSeal Corporation	EMERGENCY TELEPHONE NO.	
	2601 Spenwick Drive	Chemtrec 24 Hours	
	Houston, Texas 77055 USA	(800) 424-9300	
DATE OF PREPARATION	August 7, 2002	TECHNICAL SERVICE TELEPHONE NO.	
		(800) 231-3345	

## Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS
<20	7646-85-7	Zinc Chloride	
		ACGIH TLV	1 mg/m3
		OSHA PEL	1 mg/m3
<1	12125-02-9	Ammonium Chloride	
		ACGIH TLV	10 mg/m3
		OSHA PEL	10 mg/m3
<10	1314-13-2	Zinc Oxide	
		ACGIH TLV	5 mg/m3
		OSHA PEL	5 mg/m3
-	7440-31-5	Tin	
		ACGIH TLV	5 mg/m3
		OSHA PEL	5 mg/m3
<1	7440-36-0	Antimony	
		ACGIH TLV	0.5 mg/m3
		OSHA PEL	0.5 mg/m3

## Section 3 -- HAZARDS IDENTIFICATION

### SUMMARY OF ACUTE HAZARDS

Irritation to respiratory system from fumes evolved during soldering.  
Eye contact may cause intense irritation and injury.

### ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

#### INHALATION

Irritation to respiratory system from fumes evolved during soldering.

#### EYE CONTACT

Contact may cause intense irritation and injury.

#### SKIN CONTACT

May cause skin irritation.

#### INGESTION

Nausea, vomiting, irritation to digestive system.

### SUMMARY OF CHRONIC HAZARDS

Short term effects to liver and kidneys can occur. Chemical irritation from continued skin contact can occur. Continuous industrial use in small unventilated areas may result in sufficient inhalation of solder and flux

fumes to cause lung damage and irritation of respiratory tract.

#### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

#### Section 4 -- FIRST AID MEASURES

If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on SKIN: Immediately wash with soap and water. Remove and wash any contaminated clothing.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

#### Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
>230 F (110 C) SETA CC	N/D	N/D
EXTINGUISHING MEDIA		

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and other protective clothing. Hazardous decomposition products possible (see Section 10). May release ZnO and HCl fumes.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Heat may build up pressure and rupture closed containers.

#### Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

#### Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Store flux at ambient conditions. Wash thoroughly after handling to remove all residue.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.

#### Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: N/A

MECHANICAL (GENERAL): Acceptable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed

areas thoroughly before eating, drinking, smoking, or leaving work area.  
Launder contaminated clothing before reuse.

=====  
Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
=====

BOILING POINT: N/D  
SPECIFIC GRAVITY (H2O = 1): 1.59  
VAPOR PRESSURE (mm Hg): N/D  
MELTING POINT: N/D  
VAPOR DENSITY (AIR = 1): N/A  
EVAPORATION RATE (ETHYL ACETATE = 1): N/A  
APPEARANCE/ODOR: Gray Paste / No Odor  
SOLUBILITY IN WATER: Insoluble  
=====

Section 10 -- STABILITY AND REACTIVITY  
=====

STABILITY: Stable  
CONDITIONS TO AVOID: None  
INCOMPATIBILITY (MATERIALS TO AVOID): None known  
HAZARDOUS DECOMPOSITION PRODUCTS: Toxic fumes of zinc, chlorine, and HCL may  
be evolved during soldering.  
HAZARDOUS POLYMERIZATION: Will not occur.  
=====

Section 11 -- TOXICOLOGY INFORMATION  
=====

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.  
=====

TOXICOLOGY DATA

Ingredient Name  
=====

Zinc Chloride	Oral-Rat LD50:350 mg/kg Inhalation-Rat LCLo:1960 mg/m3/10M
Ammonium Chloride	Oral-Rat LD50:1650 mg/kg Inhalation-Rat LC50:N/D
Zinc Oxide	Oral-Rat TDLo:6846 mg/kg Inhalation-Mouse LC50:2500 mg/m3
Tin	Oral-Rat TD50:N/D Inhalation-Rat LC50:N/D
Antimony	Oral-Rat LD50:7 g/kg Inhalation-Rat TCLo:50 mg/m3/7H/52W-I

=====

Section 12 -- Ecological Information  
=====

ECOLOGICAL DATA

Ingredient Name  
=====

Zinc Chloride	Food Chain Concentration Potential	None
	WATERFOWL TOXICITY	N/A
	BOD	None
	AQUATIC TOXICITY: 7.2 ppm/96 hr/medium	bluegill/TLm
Ammonium Chloride	Food Chain Concentration Potential	None
	WATERFOWL TOXICITY	N/A

Zinc Oxide	BOD	N/A
	AQUATIC TOXICITY:	6 ppm/96 hr/sunfish TLm
	Food Chain Concentration Potential	N/D
	WATERFOWL TOXICITY	N/D
Tin	BOD	N/D
	AQUATIC TOXICITY:	N/D
	Food Chain Concentration Potential	N/D
	WATERFOWL TOXICITY	N/D
Antimony	BOD	N/D
	AQUATIC TOXICITY:	N/D
	Food Chain Concentration Potential	N/D
	WATERFOWL TOXICITY	N/D
	BOD	N/D
	AQUATIC TOXICITY:	N/D
	Food Chain Concentration Potential	N/D
	WATERFOWL TOXICITY	N/D

Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated solid waste  
 Disposal Method: Approved landfill  
 Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with Federal, State, and Local regulation regarding pollution.

Section 14 -- TRANSPORTATION INFORMATION

DOT: Non-Regulated  
 OCEAN (IMDG): Non-Regulated  
 AIR (IATA): Non-Regulated  
 WHMIS (CANADA): Non-Regulated

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA

Ingredient Name

Zinc Chloride	SARA 313	Yes
	TSCA Inventory	Yes
	CERCLA RQ	1000 lb.
	RCRA Code	N/A
Ammonium Chloride	SARA 313	No
	TSCA Inventory	Yes
	CERCLA RQ	N/A
	RCRA Code	N/A
Zinc Oxide	SARA 313	Yes
	TSCA Inventory	Yes
	CERCLA RQ	N/A
	RCRA Code	N/A
Tin	SARA 313	No
	TSCA Inventory	Yes
	CERCLA RQ	N/A
	RCRA Code	N/A
Antimony	SARA 313	Yes

TSCA Inventory	Yes
CERCLA RQ	5,000 lb.
RCRA Code	N/A

=====

Section 16 -- OTHER INFORMATION

-----

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001